



INVEST IN THE FUTURE



French manufacturer
since 1964

Chargers, Boosters & Starters

Charge & entretien des batteries

Batterieservicegeräte-Katalog

Caricabatterie, Booster & Avviatore

Catálogo de Cargadores

2
0
2
0
C

- CHARGER
- BOOSTER
- STARTER
- TESTER
- JUMPER CABLE
- ACCESSORIES





GYS FRANCE
Laval

🕒 1964
👤 × 530

Created in 1964, GYS is a French industrial group with 740 employees around the world. Built around continuous investment in Research & Development and in the acquisition of knowledge, the company is now a major player in the design and manufacture of welding machines, battery chargers and car body repair equipment.



Nicolas & Bruno Bouygues


“ The market realities are constantly changing and the size of our family business requires us to quickly adapt to new contexts and new challenges.

We are convinced that our future is closely linked to the future of our partners. This is why we do everything in our power to understand what distributors and users expect from us and what challenges they face every day. To support them in facing these challenges, we wish to become and remain their privileged partner on the path we will travel together. ”

Bruno Bouygues,
C.E.O.

A worldwide coverage

125 countries



INVEST IN THE FUTURE

FR

Créé en 1964, GYS est un groupe industriel français regroupant plus de 700 collaborateurs dans le monde. Fort d'un centre de recherche de premier plan, GYS est un acteur majeur dans la conception et la fabrication d'équipements de soudage, de chargeurs de batteries et de systèmes de réparation carrosserie.

Les nouvelles réalités du marché sont en perpétuel changement et la taille de notre entreprise familiale nous impose une adaptation rapide aux nouveaux contextes et à leurs enjeux.

Nous sommes convaincus que notre avenir est étroitement lié à celui de nos clients. Pour cela, nous mettons tout en oeuvre pour comprendre ce que les distributeurs et les utilisateurs attendent de nous, savoir à quels défis ils font face et voir dans quelle mesure nous pouvons leur permettre de les relever afin de devenir et rester leur partenaire privilégié pour le chemin que nous avons à parcourir ensemble.

DE

GYS wurde 1964 gegründet und ist ein französisches Familienunternehmen mit mehr als 700 Mitarbeitern auf der ganzen Welt. Dank einem erstklassigen Forschungszentrum ist GYS ein wichtiger Akteur in der Entwicklung und Herstellung von Schweißgeräten, Batterieladegeräten und Karosseriereparatursystemen.

Neue Marktbedingungen sind in fortwährender Veränderung und die Größe unseres Familienunternehmens veranlasst eine rasche Anpassung an neue Umstände und an ihre Herausforderungen.

Wir sind überzeugt, dass unsere Zukunft eng mit der unserer Kunden verbunden ist. Dafür setzen wir all unser Können ein, um zu verstehen, was die Händler und Anwender von uns erwarten, welchen Herausforderungen sie gegenüberstehen und um zu schauen, in welchem Maße wir sie unterstützen können, damit wir ihr bevorzugter Partner werden und bleiben auf dem Weg, den wir gemeinsam beschreiten.

IT

Nato nel 1964, GYS è un gruppo industriale francese che raggruppa oltre 700 collaboratori nel mondo. Forte di un centro di ricerca di grande importanza, GYS è uno dei maggiori protagonisti nella progettazione e fabbricazione di apparecchiature per la saldatura e il taglio, di caricabatterie booster e avviatori e sistemi di riparazione delle carrozzerie.

Le realtà del mercato sono in continuo cambiamento e richiedono risposte immediate. Le dimensioni della nostra impresa familiare consentono un adattamento rapido ai nuovi contesti e alle loro problematiche.

Siamo convinti che il nostro futuro sia strettamente legato a quello dei nostri clienti. Per questo noi mettiamo il massimo impegno per capire quello che i distributori e i loro clienti/utilizzatori si aspettano da noi, quali sfide devono affrontare e come possiamo aiutarli per farli crescere, per diventare e restare loro partner di riferimento per proseguire insieme sul cammino del successo.

👤
740 people

🏢
55 000 m²
590 000 sqf
2 factories

🇩🇪 GYS GERMANY
Aachen

🕒 2006
👤 × 60

🇬🇧 GYS U.K.
Rugby

🕒 2008
👤 × 30

🇨🇳 GYS CHINA
Shanghai

🕒 2004
👤 × 110

🇮🇹 GYS ITALIA
Venezia

🕒 2015
👤 × 10

Partners





GYS ACADEMY

Training centre dedicated to professionals

Centre de formation agréé

Trainingcenter für Profis

Centro di formazione dedicato ai professionisti

Ref. 52 53 0068153

3 catalogues

2 400+ references



Welding & Cutting



Car body Welding Systems



Chargers, Boosters & Starters

CHARGERS

Smart HF


GYSFLASH (Pb)
p.6


GYSFLASH PL (Pb/LiFePO₄/Li-ion)
p.9


GYSFLASH LITHIUM (LiFePO₄)
p.11

Connectors p.12
Selection p.13

ON BOARD

GYSFLASH E
p.14

BSU


GYSFLASH PRO
p.16


CNT Modules
p.21

Accessories p.20

Chargers

ARTIC
p.22


ENERGY & TCB
p.23


CT, CA & WATTMATIC
p.24


BATIUM
p.26

STARTERS & CHARGERS


START & NEOSTART
p.28


STARTIUM
p.30


DIAGSTARTIUM
p.31

BOOSTERS

Traditional (Pb/Lead)


GYSPACK
p.32


GYSPACK PRO
p.35


STARTPACK TRUCK
p.36


STARTPACK
p.37


ENERGYSTATION
p.39

Selection
p.40

Lithium inside


NOMAD POWER & POWER PRO
p.42

Super capacitors inside


STARTRONIC
p.46


GYSCAP
p.47

TESTERS


TBP, BT, PBT
p.48

ACCESSORIES


Power inverter
p.52


Jumper cables
p.54


Clamps & consumables
p.56

Accessories
p.57

Working lights
p.58

+ MORE

NATO/OTAN
selection
p.41


Traction selection
p.41

Charging curves
p.59

Marketing
p.59

Advanced R&D

75



Metal work
Tôlerie
Blechbearbeitung



Painting & marking
Peinture & marquage
Lackierstraße

Assembly
Montage/tests
Montage



Electronics
Électronique
Elektronik



Mechanical
Mécanique
CNC-Bearbeitung



Transformers
Transformateurs
Transformatoren



Cable work
Filerie
Kabelkonfektionierung

100%
in house
production

www.gys.fr



GYSFLASH TECHNOLOGY



SSM

Mémorisation des réglages. Redémarrage automatique en cas de coupure électrique.

Save and load settings. Automatic restart in case of power cut.

Einstellungsspeicherung. Automatisches Starten nach einem Netzausfall.

START STOP

Start/stop Engine :

Compatible véhicules Start/Stop.

Compatible with Start/Stop vehicles.

Geeignet für START-STOP- Fahrzeuge.

CAN BUS

Can bus ready : compatible avec la technologie Can Bus, le Gysflash se branche directement sur la prise 12 V de la moto (câble en option).

Can Bus ready: compatible with Can Bus Technology, the Gysflash can be connected to the motorcycle 12V socket (cable is optional).

Can-Bus Ready: Mit der Can-Bus Technologie kompatibel. Das GYSFLASH wird direkt an den 12V-Anschluss des Motorrads angeschlossen (Kabel optional).

Auto Recovery

Auto Recovery : Récupération des éléments des batteries profondément déchargées (mini 2V) et/ou sulfatées.

Auto Recovery : Recovers deeply discharged (min 2V) and/or sulfated batteries.

Auto Recovery: Wiederherstellung der Zellen bei tiefentladenen bzw. sulfatierten Batterien (min. 2V).

Cold Charge

Mode "Cold charge" : optimisation des performances en cas de temps froid ou de gel.

"Cold charge" mode: performance-enhancing charging mode for cold or freezing weather conditions.

Cold Charge-Modus: Leistungsoptimierung bei kaltem Wetter oder bei Frost.

Temp

Équipé d'un capteur haute sensibilité, le Gysflash ajuste automatiquement les paramètres de charge en fonction de la température ambiante.

Fitted with a highly sensitive sensor, Gysflash automatically adjusts the charge based on ambient temperature.

Ausgestattet mit einem hochempfindlichen Sensor stellt das GYSFLASH automatisch die Ladeparameter der Umgebungstemperatur entsprechend ein.

REFRESH

Rééquilibrage des cellules de la batterie pour plus de longévité (suivant modèle).

Rebalancing of the battery cells for greater longevity (not available on all models).

Regenerierung der Batteriezellen für eine längere Lebensdauer (je nach Modell).

Power Supply

Source d'énergie : mode de maintien optimal de l'état de charge. Idéal pour les véhicules en hivernage, de démonstration, ou pour le remplacement de batterie.

Power supply mode: Optimum floating charge, ideal for use during battery change to protect vehicle memory.

Also for when the vehicle is not in use for extended periods or for demonstration use.

Energiequelle: Aufrechterhaltung des Batteriezustands. Ideal für Saison-, Ausstellungsfahrzeuge oder bei Batteriewechsel.



GYSFLASH

CHARGERS Pb

SMART HF INVERTER

BEST SELLER



IP 65

WATER PROTECTION

GYSFLASH

1.12, 4.12, 6.12, 8.12, 12.12,
6 HERITAGE, 6.24, 9.24, 1.12 PL,
6.24 PL, 3.48 PL,
1.12 Lithium, 6.12 Lithium



12V

GYSFLASH 1.12

1 A

GO > 7 V



F FLASH Connector



029361
029514

GYSFLASH 4.12

0.8/4 A

GO > 2 V



F FLASH Connector



029422
029521

GYSFLASH 6.12

0.8/6 A

GO > 2 V



F FLASH Connector



029378
029513

GYSFLASH 8.12

8 A

GO > 2 V



S SAE Connector



029385
029545

GYSFLASH 12.12

12 A

GO > 2 V



S SAE Connector



029392
029552



DISPLAY BOX

GYSFLASH 4.12 x 5

026001

	PATENTS REGISTERED NUMBERS 002280008 & 002279927 EUROPEAN TRADEMARK & DESIGN	50/60 Hz	Power	I _{charge}	V	Charge	Maintenance	Zz	Ondulation/ Ripple	Charging curve	IP	Weight	Dimensions
GYSFLASH 1.12			18 W	1 A	12V	2 > 32 Ah	2 > 100 Ah	<0.4 Ah/month	<150 mV Rms	IuU	7 steps	IP 65	0.44 kg 130 × 80 × 38 mm
GYSFLASH 4.12			70 W	0,8/4 A	12V	1.2 > 90 Ah	1.2 > 125 Ah	<0.4 Ah/month	<150 mV Rms	IuU	7 steps	IP 65	0.69 kg 170 × 90 × 51 mm
GYSFLASH 6.12			90 W	0,8/6 A	12V	1.2 > 125 Ah	1.2 > 170 Ah	<0.4 Ah/month	<150 mV Rms	IuU	8 steps	IP 65	0.77 kg 190 × 100 × 52 mm
GYSFLASH 8.12			130 W	8 A	12V	15 > 160 Ah	15 > 240 Ah	<0.4 Ah/month	<150 mV Rms	IuU	8 steps	IP 65	0.85 kg 190 × 100 × 52 mm
GYSFLASH 12.12			195 W	12 A	12V	20 > 250 Ah	20 > 330 Ah	<0.4 Ah/month	<100 mV Rms	IuU	8 steps	IP 65	1.1 kg 221 × 111 × 58 mm

DESIGN
GYS
FRANCE

MADE IN
GYS CHINA

GYSFLASH

SMART HF INVERTER CHARGERS

LiFePO₄



UVP Wake up (Under Voltage Protection)
Réactivation de la batterie en protection UVP.
Battery reactivation when in UVP protection.
Reaktivierung der Batterie mit UVP-Schutz.



Equalizing Balancing System
Équilibrage des cellules.
Balancing of the battery cells.
Ausgleich der Batteriezellen.



GYSFLASH

CHARGERS Pb


SMART HF INVERTER



OPTION

Gysflash 18.12 PL, 30.12 PL, 20.12/24 PL, 10.36/48 PL

Magnetfix 20
026063



GYSFLASH

SMART HF INVERTER CHARGERS

9

HERITAGE • 6 / 12 V

6 / 12 / 24 V

12 V

12 / 24 V

GYSFLASH 6 HERITAGE

0.8/6A GO > 2 V



GYSFLASH 6.24

0.8/6A GO > 2 V



GYSFLASH 9.24

9A GO > 2 V



GYSFLASH 1.12 PL

1A GO > 7 V



GYSFLASH 18.12 PL

7/12/18A GO > 2 V



GYSFLASH 30.12 PL

7/15/30A GO > 2 V



GYSFLASH 20.12/24 PL

7/15/20A GO > 2 V



GYSFLASH	Power	I _{charge}	V	Charge	Maintenance	Zz	Ondulation/Ripple	Charging curve	IP	Weight	Dimensions	PATENTS REGISTERED NUMBERS		
												002280008 & 002279927	EUROPEAN TRADEMARK & DESIGN	
GYSFLASH 6 HERITAGE	220-240 V AC	2 m	90 W	0.8/6 A	6/12 V	1.2, 125 Ah	1.2, 170 Ah	<0.4 Ah/month	<150 mV Rms	IUoU	8 steps	IP 65	0.77 kg	190 × 100 × 52 mm
GYSFLASH 6.24	220-240 V AC	2 m	130 W	0.8/6 A	6/12 V	1.2, 125 Ah	1.2, 170 Ah	<0.4 Ah/month	<150 mV Rms	IUoU	7 step	IP 65	0.85 kg	190 × 100 × 52 mm
				0.8/4 A	24 V	1.2, 100 Ah	1.2, 140 Ah							
GYSFLASH 9.24	220-240 V AC	2 m	190 W	9 A	6/12 V	18, 220 Ah	18, 300 Ah	<0.4 Ah/month	<100 mV Rms	IUoU	8 step	IP 65	1.1 kg	221 × 111 × 58 mm
				6 A	24 V	15, 125 Ah	15, 170 Ah							

GYSFLASH	Power	I _{charge}	V	Charge	Maintenance	Zz	Ondulation/Ripple	Charging curve	IP	Weight	Dimensions	PATENTS REGISTERED NUMBERS		
												002280008 & 002279927	EUROPEAN TRADEMARK & DESIGN	
GYSFLASH 1.12 PL	220-240 V AC	2 m	20 W	1 A	12 V									
GYSFLASH 18.12 PL	220-240 V AC	2 m	300 W	7/12/18 A	12 V	15, 270 Ah (Pb) 7, 270 Ah (LiFePO4)	2, 100 Ah (Pb) 0.5, 50 Ah (LiFePO4)	<0.5 Ah/month	<100 mV Rms	IUoU	7 step (Pb) 8 step (LiFePO4)	IP 43	1.55 kg	190 × 190 × 73 mm
GYSFLASH 30.12 PL	220-240 V AC	2 m	500 W	7/15/30 A	12 V	15, 375 Ah (Pb) 7, 375 Ah (LiFePO4)		<0.5 Ah/month	<150 mV Rms	IUoU	7 step (Pb) 8 step (LiFePO4)	IP 43	1.85 kg	190 × 190 × 73 mm
GYSFLASH 20.12/24 PL	220-240 V AC	2 m	500 W	7/15/20 A	12 V	15, 300 Ah (Pb) 7, 300 Ah (LiFePO4)		<1 Ah/month	<150 mV Rms	IUoU	7 step (Pb) 8 step (LiFePO4)	IP 43	1.85 kg	190 × 190 × 73 mm
				7/15 A	24 V	15, 240 Ah (Pb) 7, 240 Ah (LiFePO4)								

DESIGN GYS FRANCE
MADE IN GYS CHINA
8

DESIGN GYS FRANCE
MADE IN FRANCE



CHARGERS

SMART HF INVERTER

Pb/Lithium

ELECTRICAL MOBILITY

LiFePO₄ / Li-ion / Li-Po / NMC / LCO / MCO / NCA...



54.0V :	LFP	Li
	15 serial cells	13 serial cells
58.0V :	LFP	Li
	16 serial cells	14 serial cells

24V • ELECTRICAL MOBILITY

48V • INDUSTRY / ELECTRICAL MOBILITY • 36/48V

GYSFLASH 6.24 PL

6A GO > 2V

SSM, t°

7 STEP Pb, 8 STEP LiFePO₄

S SAE Connector

1.45 m, Ø6, 0.45 m

027398

GYSFLASH 3.48 PL

3A GO > 5V

SSM, t°

7 STEP Pb, 8 STEP LiFePO₄

S SAE Connector

1.45 m, Ø6, 0.45 m

027893

GYSFLASH 10.36/48 PL

10A GO > 5V

SSM, t°

7 STEP Pb, 8 STEP LiFePO₄

A ANDERSON Connector

1.9 m (4 mm²)

027060, 027916

OPTION Magnetfix 20 026063

×4

MOBILITY



OUTDOOR



MEDICAL



INDUSTRY



CHARGERS

SMART HF INVERTER

LiFePO₄



12V

GYSFLASH 1.12 Lithium

1A GO > 7V

SSM, CAN BUS

8 STEP LiFePO₄

F FLASH Connector

1.45 m, Ø6, 0.45 m

029675

GYSFLASH 6.12 Lithium

4/6A GO > 2V

SSM, CAN BUS

8 STEP LiFePO₄

F FLASH Connector

1.45 m, Ø6, 0.45 m

029729

DESIGN GYS FRANCE

MADE IN GYS CHINA

MADE IN FRANCE

	50/60 Hz	Power	I _{charge}	V	Charge	Maintenance	Zz	Ondulation/Ripple	Charging curve	IP	Weight	Dimensions		
GYSFLASH 1.12 Lithium	220-240 V AC	1 m	18 W	1A	12V	0.5 > 20 Ah	0.5 > 50 Ah	<0.4 Ah/month	<150 mV Rms	IUoU	8 step	IP 65	0.44 kg	130 × 80 × 38 mm
GYSFLASH 6.12 Lithium	220-240 V AC	2 m	90 W	4/6 A	12V	1.2 > 125 Ah	1.2 > 170 Ah	<0.4 Ah/month	<150 mV Rms	IUoU	8 step	IP 65	0.77 kg	190 × 100 × 52 mm



DESIGN GYS FRANCE

MADE IN GYS CHINA

MADE IN FRANCE

	50/60 Hz	Power	I _{charge}	V	Charge	Maintenance	Zz	Ondulation/Ripple	Charging curve	IP	Weight	Dimensions		
GYSFLASH 6.24 PL	220-240 V AC	2 m	190 W	6A	24V	15 > 125 Ah (Pb) 2 > 125 Ah (Li)	15 > 170 Ah (Pb) 2 > 170 Ah (Li)	<0.4 Ah/month	<150 mV Rms	IUoU	7 step (Pb) 8 step (Li)	IP 65	1,1 kg	221×111×58 mm
GYSFLASH 3.48 PL	220-240 V AC	2 m	195 W	3A	48V	6 > 60 Ah 3 > 60 Ah	6 > 85 Ah 3 > 85 Ah	<0.4 Ah/month	<150 mV Rms	IUoU	7 step (Pb) 8 step (Li)	IP 65	1,1 kg	221×111×58 mm
GYSFLASH 10.36/48 PL	220-240 V AC	2 m	500 W	10A 8A	36V 48V	20 > 230 Ah (Pb) 10 > 230 Ah (Li) 15 > 160 Ah (Pb) 8 > 160 Ah (Li)		<0.4 Ah/month	<150 mV Rms	IUoU	7 step (Pb) 8 step (Li)	IP 43	1,85 kg	190×190×73 mm

CONNECTORS

Une solution complète
A complete solution
Eine Komplettlösung



F Flash Connector

GYSFLASH ≤ 6A : 1.12 / 4.12 / 6.12 / 6 Heritage / 6.24 / 1.12 Li / 6.12 Li / 1.12 PL

F1 / Clamps L 0.45 m (1.3mm ²) All 026889	F2 / Charge indicator L 0.56 m (1.3mm ²) All LEAD 029149	F3 / Eyelets ø M6 L 0.45 m (1.3mm ²) All LEAD 029194 ø M8 L 0.45 m (1.3mm ²) 24V 36V 48V 027626	F4 / Charge indicator eyelets ø M6 L 0.56 m (1.3mm ²) All LEAD 029200
---	---	---	--

F5 / Cigarette lighter L 0.45 m (0.82mm ²) 029439	F6 / Cable L 2.50 m (1.3mm ²) All 029057	F7 / Connector MLX L 0.45 m (1.3mm ²) 027589	F8 Adapter S / F - F / S L 0.45 m (1.3mm ²) 027480	F9 Adapter F / A L 0.45 m (1.3mm ²) 025820
--	--	---	---	---

S SAE Connector

GYSFLASH < 16A : 12.12 / 9.24 / 6.24 / 3.48 PL

S1 / Clamps L 1.50 m (1.3mm ²) All +Showroom Gysflash 1212 027688	S2 / Eyelets ø M6 L 0.45 m (1.3mm ²) 12V 24V 027466 ø M8 L 0.45 m (1.3mm ²) 24V 36V 48V 027633 ø M10 L 0.45 m (1.3mm ²) 36V 48V 027640	S3 / XLR 3 pin L 0.45 m (1.3mm ²) 027428	S4 / T-Bar L 0.45 m (1.3mm ²) 027442
--	--	---	---

S5 Adapter S / A L 0.45 m (1.3mm ²) 027473	S6 KIT SAE / JACK (max 5 A) L 0.45 m (1.3mm ²) 025646
---	--

A ANDERSON Connector

GYSFLASH < 40A : 18.12 PL / 30.12 PL / 20.12-24 PL / 10.36-48 PL

A1 / Clamps All L 1.90 m (4mm ²) 026094 L 6 m (4mm ²) 027435	A2 / Eyelets 4mm ² ø M6 L 0.40 m 12V 24V 027657 ø M8 L 0.40 m 24V 36V 48V 027664 ø M8 L 1.90 m 24V 36V 48V 027794 ø M10 L 0.40 m 36V 48V 027671	A3 L 1.5 m (4mm ²) 027855	A4 x2 x2 x4 2 connectors 027800
--	--	--	---

SELECT THE RIGHT GYSFLASH

CHOISISSEZ VOTRE GYSFLASH • WÄHLEN SIE IHR GYSFLASH AUS

Contact us for special projects



GYSFLASH	MEDICAL SERVICE - LEISURE					MOTORBIKE LIGHT MOBILITY				AUTO - CAMPER VAN - TRUCK										MARINE			INDUS TRY	URBAN		
	6V	12V	24V	36V	48V																					
Pb																										
1.12																										
1.12 PL																										
4.12																										
6.12																										
8.12																										
12.12																										
18.12 PL																										
30.12 PL																										
6 Heritage	6V	12V																								
6.24 PL																										
20.12/24 PL																										
6.24	6V	12V	24V																							
9.24																										
3/48 PL																										
10.36/48 PL																										
LiFePO4																										
1.12 Lithium																										
1.12 PL																										
6.12 Lithium																										
18.12 PL																										
30.12 PL																										
6.24 PL																										
20.12/24 PL																										
3/48 PL																										
10.36/48 PL																										
Li-ion																										
6.24 PL																										
3/48 PL																										
10.36/48 PL																										

M = maintenance only

SMART COOLING TECHNOLOGY

- 100% DUST PROOF
- SILENT

HIGH EFFICIENCY
Up to 15%
Energy Saving
93%
EMC class B

[ALU] RUST PROTECTION

ULTRA LIGHT

VIBRATION & SHOCK RESIST

-25 / +60°C

GYSFLASH PL-E TECHNOLOGIES

SSM
Mémorisation des réglages. Redémarrage automatique en cas de coupure électrique.
Save and load settings. Automatic restart in case of power cut.
Einstellungsspeicherung. Automatisches Starten nach einem Netzausfall.




Auto Recovery : Récupération des éléments des batteries profondément déchargées (mini 2V) et/ou sulfatées.
Auto Recovery : Recovers deeply discharged (min 2V) and/or sulfated batteries.
Auto Recovery: Wiederherstellung der Zellen bei tiefentladenen bzw. sulfatierten Batterien (min. 2V).

t°
Équipé d'un capteur haute sensibilité, le Gysflash ajuste automatiquement les paramètres de charge en fonction de la température ambiante.
Fitted with a highly sensitive sensor, Gysflash automatically adjusts the charge based on ambient temperature.
Ausgestattet mit einem hochempfindlichen Sensor stellt das GYSFLASH automatisch die Ladeparameter der Umgebungstemperatur entsprechend ein.

LiFePO₄

Equalizing Balancing System
Équilibrage des cellules. Balancing of the battery cells. Ausgleich der Batteriezellen.


SMART CHARGE



GYSFLASH PRO
CHARGERS ON BOARD SUPPORT UNIT
EMBARQUÉ ON BOARD

Pb/Lithium ✓ LiFePO₄ / Li-ion / Li-Po / NMC / LCO / MCO / NCA...

PFC POWER FACTOR CORRECTION
185 V ← 265 V



12 V

GYSFLASH 18.12 PL-E
18 A Pb/LFP
PFC SSM t° EAS
025806



24 V

GYSFLASH 15.24 PL-E
15 A Pb/Traction/LFP/Li-ion
PFC SSM t° EAS
025943



36 / 48 V

GYSFLASH 10.36/48 PL-E
10 A Pb/Traction/LFP/Li-ion
PFC SSM t° EAS
025950



MADE IN FRANCE	50 / 60 Hz	START MINI	I _{max}	25°C @ 100%	40°C @ 100%	50°C @ 100%	60°C @ 100%	Battery		Zz	Ondulation/Ripple	IP	1 2 3	Weight		
								Pb	LFP							
GYSFLASH 18.12 PL-E	230V	12V	300W	2V	18A	18A	16A	14A	12.5A	36 > 270 Ah	18 > 270 Ah	<0.4 Ah/month	<150 mV Rms	20	21.5 × 7 × 17.5 cm	1.3 kg
GYSFLASH 15.24 PL-E	230V	24V	500W	2V	15A	15A	13.5A	11.5A	9A	30 > 240 Ah	15 > 240 Ah	<0.4 Ah/month	<150 mV Rms	20	21.5 × 8 × 17.5 cm	1.3 kg
GYSFLASH 10.36/48 PL-E	230V	36V / 48V	500W	2V	10A / 8A	10A / 8A	9A / 7A	7.5A / 6A	6A / 5A	20 > 230 Ah / 15 > 160 Ah	10 > 230 Ah / 8 > 160 Ah	<0.4 Ah/month	<150 mV Rms	20	21.5 × 8 × 17.5 cm	1.3 kg



Homologations Approvals Zulassungen



ACCESSIBILITY

22 languages

- GB, SE, PL, FR, DK, SK, DE, FI, UA, NL, TR, HU, ES, HR, PT, GR, IT, CZ, RU, + CN (simplified & traditional) & JP integrated

HIGH EFFICIENCY Up to 15% Energy Saving 93% EMC class B

BSU & CHARGERS BATTERY SUPPORT UNIT




Select mode, Select parameters, Adjust values

CHARGING TECHNOLOGY


SMART 9 STEP

Pb



- 1. Status analysis, 2. Recovery, 3. Sulphation test, 4. Desulfation, 5. Fast charge 80%, 6. Absorption, 7. Test Absorption, 8. Refresh, 9. Floating 100%

LiFePO4



- 1. Status analysis, 2. UVP Wake Up, 3. Recovery, 4. Fast charge 90%, 5. Absorption 95%, 6. Test, 7. Completion, 8. Equalization, 9. Floating 100%

CHARGE

Pb AUTOMOTIVE

- GEL, AGM, LIQUID, EASY, EXPERT, NORMAL, BOOST, RECOVERY+

Pb TRACTION

LIQUID, GEL

LITHIUM READY

- LFP/LiFePO4, LI-ION STD, LFP CELL+, LI-ION CELL+

TEST

- VOLTAGE, START UP, ALTERNATOR

BSU

DIAG+



SHOWROOM



CHANGE BATTERY



POWER SUPPLY



LITHIUM

- LFP, LI-ION

STARTER

START

PFC POWER FACTOR CORRECTION



FV FLEXIBLE VOLTAGE



SMART COOLING TECHNOLOGY

100% DUST PROOF



SILENT



GYSFLASH 30.12, GYSFLASH 50.12 FV, GYSFLASH 100.12, GYSFLASH 101.12 CNT, GYSFLASH 30.24, GYSFLASH 50.24



10.5 cm

GYSFLASH 30.12, GYSFLASH 50.12 FV, GYSFLASH 100.12, GYSFLASH 101.12 CNT, GYSFLASH 30.24, GYSFLASH 50.24

13 cm

GYSFLASH 121.12 CNT FV, GYSFLASH 101.24 CNT FV

12 V



GYSFLASH 30.12 30 A



2.5 m - 6 mm² 029224

GYSFLASH 50.12 FV 50 A



2.5 m - 10 mm² 026056

GYSFLASH 100.12 100 A



2.5 m - 16 mm² 029071

GYSFLASH 101.12 CNT 100 A



2.5 m - 16 mm² 025790

GYSFLASH 121.12 CNT FV 120 A



5 m - 25 mm² 026971

CNT TECHNOLOGY

FUTURE PROOF SOFTWARE

USB CONNECTOR

YouTube



1 EASY SOFTWARE UPDATE

GYSFLASH evolutions



UPDATE



2 FULL DATA TRACEABILITY

Data export capabilities



DATA LOG



3 CUSTOM CONFIGURATION

CNT MANAGER

- GYSFLASH parameters, Custom curves, Multi products management, Import/export configurations



PERSONAL CONFIG



EXTREME MODULARITY

SMC (SMART MODULE CONNECTOR)



Details p.21

SPECIAL PROJECT

Contact us for special projects. Quick customization : modes, curves, parameters, and more...

6 / 12 / 24 V



GYSFLASH 30.24 30 A

2.5 m - 6 mm² 029231

GYSFLASH 50.24 50 A

2.5 m - 10 mm² 029095, 5 m - 16 mm² 029620

GYSFLASH 101.24 CNT FV 100 A

5 m - 25 mm² 025967

MADE IN FRANCE

Table with columns: Input Voltage, Length, Width, Height, Power, Start, I max, Efficiency at 25°C and 40°C, Capacity, IP, Dimensions, Weight, CNT status



BSU & CHARGERS

BATTERY SUPPORT UNIT

PFC POWER FACTOR CORRECTION
185 V ← 265 V
110 V 230 V

FV FLEXIBLE VOLTAGE
85 V ← 265 V
110 V 230 V

SMART COOLING TECHNOLOGY

100% DUST PROOF

SILENT



GYSFLASH 102.12, 32.12 PL, 15.24 XTREM



XTREM



NEW
10/2020

SHOCK RESISTANT

IP 65
INDOOR / OUTDOOR

12 V • VERTICAL



GYSFLASH 102.12

100 A

PFC

5 m - 16 mm²
029606



GYSFLASH 123.12 CNT FV

120 A

PFC FV CNT Technology

5 m - 25 mm²
025677

6 / 12 / 24 V • VERTICAL



GYSFLASH 103.24 CNT FV

100 A

PFC FV CNT Technology

5 m - 25 mm²
025684

6/12/24/36/48 V • VERTICAL



GYSFLASH 53.48 CNT FV

50 A

PFC FV CNT Technology

5 m - 25 mm²
025998

NEW
01/2021

12 V • VERTICAL

GYSFLASH 32.12 PL

30 A

7 STEP Pb
8 STEP LiFePO₄
2.5 m - 6 mm²
027381



12 / 24 V • VERTICAL

GYSFLASH 15.24 XTREM

15 A

5 m - 4 mm²
025813



ROBUST & SAFE
2 pts connection

Double insulation

OPTION

2pts/NATO
5 m - 4 mm²
025837

2pts/DIN 14690
Special emergency vehicle
028777

INCLUDED

Fixation


- ✓ GYSFLASH :
- ✓ 32.12 PL
- ✓ 102.12
- ✓ 123.12 CNT
- ✓ 103.24 CNT
- ✓ 15.24 XTREM



OPTION

MAGNETFIX 50
029637

- ✓ for GYSFLASH :
- ✓ 32.12 PL
- ✓ 102.12
- ✓ 123.12 CNT
- ✓ 103.24 CNT
- ✓ 15.24 XTREM



MADE IN FRANCE	50 / 60 Hz	L	mm ²	BATTERY	START MINI	I _{max}	25°C @ 100%	40°C @ 100%	TRACTION BATTERIES	IP	Weight	CNT		
GYSFLASH 102.12	230V	5 m	16	12V	1600W	2V	100 A	75 A	66 A	20 × 1200 Ah	41	12 × 34,5 × 29,5 cm	9,1 kg	—
GYSFLASH 123.12 CNT FV	85 > 265 V	5 m	25	12V	2000W	2V	110 V : 100 A 230 V : 120 A	100 A	85 A	20 × 1500 Ah	30	34 × 25 × 15 cm	10,4 kg	•
GYSFLASH 103.24 CNT FV	85 > 265 V	5 m	25	6/12V	3200W	2V	110 V : 100 A 230 V : 100 A	100 A	68 A	20 × 1200 Ah	30	34 × 25 × 15 cm	10,4 kg	•
				24V				100 A	79 A					
GYSFLASH 53.48 CNT FV	85 > 265 V	5 m	25	6/12/24V	3200W	2V	110 V : 50 A 230 V : 50 A	50 A	47 A	20 × 600 Ah	30	34 × 25 × 15 cm	10,4 kg	•
				36/48V				95 A	72 A					
GYSFLASH 32.12 PL	230V	2,5 m	6	12V	500W	2V	30 A	30 A	25 A	10 × 400 Ah	41	8 × 25 × 20 cm	4,9 kg	—
GYSFLASH 15.24 XTREM	230V	2,5 m	4	12/24V	500W	2V	15 A	15 A	15 A	5 × 240 Ah	65	7,5 × 25 × 21 cm	5 kg	—

ACCESSORIES

CABLES

	12 V		6/12/24V	VERTICAL		
	30.12 50.12 FV 100.12 101.12 CNT	101.24 CNT FV 121.12 CNT FV	30.24 50.24	12 V	6/12/24V	12/24 V
Anderson						
Anderson/Clamps 2.5 m - 16 mm ² 056503	✓	—	✓	✓	—	—
5 m - 16 mm ² 054615	✓	—	✓	✓	—	—
8 m - 16 mm ² 056572	✓	—	✓	✓	—	—
Anderson/NATO 5 m - 16 mm ² 026810	✓	—	✓	✓	—	—
Texas						
Texas/Clamps 2.5 m - 25 mm ² 028876	—	✓	—	—	✓	✓
5 m - 25 mm ² 027886	—	✓	—	—	✓	✓
Texas/REMA 5 m - 25 mm ² 025714	—	✓	—	—	✓	✓
Texas/Anderson 175A 5 m - 25 mm ² 025721	—	✓	—	—	✓	✓
Texas/NATO 5 m - 25 mm ² 025707	—	✓	—	—	✓	✓
XTREM						
2pts/Clamps 5 m - 4 mm ² 028760	—	—	—	—	—	✓
2pts/NATO 5 m - 4 mm ² 025837	—	—	—	—	—	✓
2pts/DIN14690 5 m - 2.5 mm ² 028777	—	—	—	—	—	✓
NATO CONNECTOR 026780						
DIN14690 CONNECTOR 028784						
Anderson<->Texas adapter 0.2 m, 16 mm ² 055902 1 m, 16 mm ² 028791						

SUPPORTS

Chariot - Trolley - Fahrwagen



Option
Cable
support
052284

NEW
10/2020 ✓ all GYSFLASH

Tablette - Wall support -
Wandhalterung



Valise de chantier
Heavy-duty case
Hartschalenkoffer

↳ 21 x 43 x 57 cm
3.9 kg
060432



FUSES

INTERNAL		EXTERNAL	
x2 40 A for GYSFLASH 30 054646	x2 125 A for GYSFLASH 100, 101, 102 054585	x5 6.3 A GYSFLASH 30 054578	10 A for GYSFLASH 40, 50, 100, 101, 102 056527

SMC CABLE






SMC cable, 3 m
025691

CNT
ACCESSORIES



Example of use



CNT MODULES

1 PRINT & SCAN

CNT-SPM
Smart Printer Module
026919



- included
- Standard roller x2
57mm x 7.5 m, Ø 25 mm
056633
 - SMC cable
0.5 m

1 - Customer data
2 - Battery data
3 - Charge data
4 - Printing

OPTIONS



- included
- USB Keyboard
AZERTY 027725
QWERTY 027770
QWERTZ compatibility

2 LIGHT & SOUND

CNT-SLM
Smart Light Module
027978



- included
- Pb charge
 - Lithium charge
 - SMC cable, 0.5 m

OK
Error

3 COMMUNICATION

CNT-SUM
Smart USB Module
025974




- included
- SMC cable
0.5 m

COMING SOON Smart Communication Module

4 EXPANSION HUB

CNT-SHM
Smart Hub Module
025981



- included
- SMC cable, 0.5 m

UPTO 4 MODULES + 4 GYSFLASH

5 MEASURE & AUTOMATE

COMING SOON Smart Extender Module

6 SPECIAL PROJECT

Contact us for special CNT modules development

PACKS GYSFLASH CNT

	101.12 CNT	121.12 CNT	CNT-SPM	Barcode Scanner	Support Scanner	AZERTY	QWERTY	Trolley	Roller
pack GYSFLASH CNT 1 027817	026988	—	026919	027718	025745	—	027770	027749	056633
pack GYSFLASH CNT 2 027824	026988	—	026919	027718	025745	027725	—	027749	056633
pack GYSFLASH CNT 3 027831	—	026971	026919	027718	025745	—	027770	027749	056633
pack GYSFLASH CNT 4 027848	—	026971	026919	027718	025745	027725	—	027749	056633





CHARGERS

ARTIC



IP 65
WATER PROTECTION
ARTIC 1500, 4000 & 8000

SSM

Mémorisation des réglages. Redémarrage automatique en cas de coupure électrique.

Save and load settings. Automatic restart in case of power cut.

Einstellungsspeicherung. Automatisches Starten nach einem Netzausfall.

START STOP

Start/stop Engine : Compatible véhicules Start/Stop. Compatible with Start/Stop vehicles.

Geeignet für START-STOP-Fahrzeuge.

Cold Charge

Mode "Cold charge": optimisation des performances en cas de temps froid ou de gel.

"Cold charge" mode: performance-enhancing charging mode for cold or freezing weather conditions.

-Cold Charge-Modus: Leistungsoptimierung bei kaltem Wetter oder bei Frost.



AUTOMATIC SMART HF INVERTER

REGULATED
I_{VOU}
FAST CHARGE

ARTIC 800
12V 0.8A GO > 7V
SSM
029569
029682



ARTIC 1500
12V 1.5A GO > 7V
SSM
029576
029699



ARTIC 4000
6/12V 4/1-4A GO > 2V (6V)
GO > 7V (12V)
SSM START STOP Cold Charge
029583
029705



ARTIC 8000
2/8A 12V GO > 7V
SSM START STOP Cold Charge
029590
029712



ENERGY

PATENTS REGISTERED NUMBERS
001652090-0001
EUROPEAN TRADEMARK & DESIGN



12V • TRADITIONAL W

ENERGY 124
3A
SSM
023215
025141



ENERGY 126
4A
SSM
023222
025165



TCB

PATENTS REGISTERED NUMBERS
001652090-0001
EUROPEAN TRADEMARK & DESIGN



12V • AUTOMATIC WU

TCB 60
2/4A GO > 3.5V
SSM START STOP
023253
025189



TCB 90
2/5.5A GO > 3.5V
SSM START STOP
023260
025202



TCB 120
3.5/7A GO > 3.5V
SSM START STOP
023284
025240



Fuse X10
10A 054530
15A 054493

RECOMMENDATION	5 Ah		10 Ah		15 Ah		20 Ah		40 Ah		80 Ah		90 Ah		110 Ah		120 Ah		180 Ah		240 Ah		300 Ah		+
	6V	12V	24V	6V	12V	24V	6V	12V	24V	6V	12V	24V	6V	12V	24V	6V	12V	24V	6V	12V	24V	6V	12V	24V	
ARTIC 800				1.6	2.5																				
ARTIC 1500				1.6	3																				
ARTIC 4000				3																					
ARTIC 8000				2																					
ENERGY 124																									
ENERGY 126																									
TCB 60																									
TCB 90																									
TCB 120																									

INCLUDED

all ARTIC



Pinces / Clamps / Klemmen 35 cm 026865



START / NEOSTART

CHARGERS & STARTERS

SSM SELF START MEMORY



12V • AUTOMATIC W2

STARTUP 80
17 A

SSM

024922
025127



12V

12/24V • TRADITIONAL

W

START 200
18 A

SSM

1.5 m - 6 mm²
025530



START 300
23 A

SSM

2 m - 10 mm²
025547



NEOSTART 320
9 / 40 A

SSM

2 m - 10 mm²
025301



NEOSTART 420
40 A

SSM

1.8 m - 10 mm²
025295
025479



NEOSTART 620
60 A

SSM

1.8 m - 16 mm²
025288
025486



12/24V • AUTOMATIC W2

GYSTART 1224 T
70 A

400 V TRI SSM

2.5 m - 35 mm²
025394



Fuse x2



50 A Start 200 054622
80 A Start 300 054653
150 A Neostart 320 054639
200 A Neostart 420, 620 & Gystart 1224 T 054547

DESIGN GYS FRANCE

MADE IN GYS CHINA

MADE IN FRANCE 28

Model	Voltage	I ₁	CHARGE W	START kW	CHARGE							START		Dimensions	Weight			
					Reg	Efficace / RMS (EN 60335)	Moyen / Average (EN 60335)	Boost	Automatic	Manual	min - max	1V/C	0V/C					
START UP 80	230V	13 A	12V	350	1	2	13,5-25 A	9 A	17 A	•	—	40 · 170 Ah	50 A	80 A	—	—	12 × 18 × 32 cm	4,4 kg
START 200	230V	13 A	12V	390	1,4	3	15-25 A	11 A	18 A	—	•	53 · 240 Ah	80 A	120 A	—	50 A	37 × 26 × 18 cm	8 kg
START 300	230V	13 A	12V	800	3,6	3	13-36 A	10 A	23 A	—	•	42 · 300 Ah	100 A	165 A	—	80 A	43 × 33 × 23 cm	13,8 kg
			24V	1 200	3,6			8 A	17 A									
NEOSTART 320	230V	13 A	12/24V	800	6,5	3	40 A	10 A	40 A	—	•	20 · 700 Ah	160 A	270 A	—	150 A	41 × 30 × 21 cm	14,7 kg
NEOSTART 420	230V	16 A	12/24V	1700	9	3	70 A	20 A	40 A	—	•	20 · 1000 Ah	300 A	420 A	—	200 A	47 × 32 × 27 cm	20,9 kg
NEOSTART 620	230V	16 A	12/24V	2000	10	3	90 A	30 A	60 A	—	•	20 · 1350 Ah	360 A	620 A	—	200 A	47 × 32 × 27 cm	24 kg
GYSTART 1224 T	400 V (TRI)	16 A	12/24V	2500	20	3	80 A	70 A	—	•	•	65 · 1350 Ah	780 A	1200 A	•	2x200 A	42,5 × 34,5 × 71 cm	54,5 kg

RECOMMENDATION



Model	6V	12V	24V	5 Ah	10 Ah	15 Ah	20 Ah	40 Ah	80 Ah	90 Ah	110 Ah	120 Ah	180 Ah	240 Ah	300 Ah	+ Ah
START UP 80	•							35 > 50 Ah								
START 200	•							35 > 50 Ah	40 · 80 Ah							
START 300	•	•						35 > 50 Ah	50 · 100 Ah							
NEOSTART 320	•	•						50 · 80 Ah		80 · 120 Ah						
NEOSTART 420	•	•	•					Precharge (± 10 mm)		50 · 120 Ah	120 · 160 Ah					
NEOSTART 620	•	•	•							60 · 180 Ah			180 · 200 Ah			
GYSTART 1224 T	•	•	•										60 · 250 Ah			



GYSPACK

BOOSTERS

Pb/Lead INSIDE

POWER SUPPLY
12V DC

COMPRESSOR



Air Kit included
4 bars



12 V **18 Ah** INSIDE HOBBIES OCCASIONAL PRO INTENSIVE

GYSPACK 400
1 250 A **1V DC**
480 A



GYSPACK AIR
1 250 A **1V DC**
480 A



12 V **22 Ah** INSIDE HOBBIES OCCASIONAL PRO INTENSIVE

GYSPACK 600
1 750 A **1V DC**
550 A



GYSPACK PRO
1 750 A **1V DC**
600 A



6 / 12 V **20 Ah + 20 Ah** INSIDE HOBBIES OCCASIONAL PRO INTENSIVE

GYSPACK HERITAGE 6/12
6V **3 200 A** **1V DC**
450 A
12V **1 600 A** **1V DC**
500 A

1.8 m - 25 mm²
600 A
025844



OPTION
MEMORY AUTO SAVE
CABLE OBD 1,5 m
054202
Fuse 7,5 A

CHARGER
Power in 110-240 V / out 12 V
50/60 Hz
054677
054660



CHARGER
Power in 110-240 V / out 12 V
50/60 Hz
054684
054691



Model	Capacity	Voltage	Start 1V/C	Cranking CC	Peak Battery	Fuse	Power Supply	EXTERNAL Charge 230V	Dimensions (cm)	Weight (kg)
GYSPACK 400	12V-18 Ah	12V	480 A	900 A	1250 A	—	12V DC/0,5A	12V/DC	26x10x29 cm	6,5 kg
GYSPACK AIR	12V-18 Ah	12V	480 A	900 A	1250 A	•	12V DC/0,5A	12V/DC	33x17x37 cm	18 kg
GYSPACK 600	12V-22 Ah	12V	550 A	1050 A	1750 A	—	12V DC	12V DC/0,5A	26x10x29 cm	6,5 kg
GYSPACK PRO	12V-22 Ah	12V	600 A	1100 A	1750 A	•	12V DC	12V DC/0,5A	35x14x37 cm	9 kg
GYSPACK HERITAGE 6/12	6V-2 x 20 Ah	6V-12V	450 A	800 A	3200 A	•	12V DC	12V DC/2A	37x20x46 cm	18 kg

RECOMMENDATION	Capacity															
	6V	12V	24V	5 Ah	10 Ah	15 Ah	20 Ah	40 Ah	80 Ah	90 Ah	110 Ah	120 Ah	180 Ah	240 Ah	300 Ah	+ Ah
GYSPACK AUTO / 400	•															
GYSPACK AIR	•															
GYSPACK 600	•															
GYSPACK PRO	•															
GYSPACK HERITAGE	•	•														



GYSPACK

BOOSTERS

Pb/Lead INSIDE

POWER SUPPLY
12V DC

NEW



12 V **28 Ah** INSIDE HOBBIES OCCASIONAL PRO INTENSIVE

GYSPACK 660

1 900 A **1V DC**
640 A

1.3 m - 25 mm² → 600 A

027862
027879



INCLUDED GYSPACK 660


CHARGER

Power in 100-240 V/out 12 V

50/60 Hz

027992

025929



12 V **28 Ah** SPIRAL INSIDE HOBBIES OCCASIONAL PRO INTENSIVE

GYSPACK 750

2 500 A **1V DC**
750 A

1.3 m - 25 mm² → 600 A

026179
026353



INCLUDED GYSPACK 750


CHARGER

Power in 110-240 V/out 12 V

50/60 Hz

054684

054691



Après chaque utilisation
After each use
Nach jeder Anwendung

DESIGN GYS FRANCE

MADE IN GYS CHINA

MADE IN FRANCE

Model	Capacity	Voltage	Current	Power	Start	Charger	Protection		Power out		Fuse	Dimensions	Weight
							ON/OFF	Memory	12V DC	Memory			
GYSPACK 660	28 Ah	12V	640 A	1200 A	1900 A	—	•	•	12V DC	—	1 × 200 A	35×19 ×40 cm / 39×23 ×45 cm	13,5 kg
GYSPACK 750	28 Ah	12V	750 A	1450 A	2500 A	—	•	•	12V DC	—	2 × 200 A	35×19 ×40 cm / 39×23 ×45 cm	13,5 kg
GYSPACK 700	16 Ah	12V	640 A	1200 A	1800 A	2.5 A	•	•	12V DC	15 A	1 × 200 A	33 × 15 × 32 cm / 35 × 24 × 36 cm	12 kg
GYSPACK 900	30 Ah	12V	830 A	1700 A	3100 A	2.5 A	•	•	12V DC	15 A	1 × 300 A	33 × 15 × 32 cm / 35 × 24 × 36 cm	16 kg

Fuse x2 **200 A** 054547 **300 A** 054561



OPTION

MEMORY AUTO SAVE
CABLE OBD 1,5 m
054202

Fuse 7,5 A



12 V **16 Ah** INSIDE HOBBIES OCCASIONAL PROFESSIONAL INTENSIVE

GYSPACK PRO 700

1 800 A **1V DC**
640 A

1.4 m - 25 mm² → 600 A

027077
027947



RENAULT
1 096 701

12 V **30 Ah** INSIDE HOBBIES OCCASIONAL PROFESSIONAL INTENSIVE

GYSPACK PRO 900

3 100 A **1V DC**
830 A

1.8 m - 35 mm² → 600 A

027084
027954



RENAULT
1 096 701

INTEGRATED CHARGER



RECOMMENDATION

Model	6V	12V	24V	5 Ah	10 Ah	15 Ah	20 Ah	40 Ah	80 Ah	90 Ah	110 Ah	120 Ah	180 Ah	240 Ah	300 Ah	+ Ah
GYSPACK 660	•															
GYSPACK 750	•															
GYSPACK 700	•															
GYSPACK 900	•															

GYSPACK BOOSTERS (Pb/Lead inside)





STARTPACK

BOOSTERS

Pb/Lead INSIDE

POWER SUPPLY
12V DC



37

STARTPACK

BOOSTERS (Pb/Lead inside)

12/24 V

22Ah + 22Ah INSIDE

HOBBIES OCCASIONAL PRO INTENSIVE

STARTPACK TRUCK			
12V	3 200 A	1V DC	750 A
24V	1 600 A	1V DC	650 A



1.8 m - 25 mm² → 600 A 025448
054639

STARTPACK TRUCK MOBILE			
12V	3 200 A	1V DC	750 A
24V	1 600 A	1V DC	650 A

1.8 m - 25 mm² → 600 A 026025
028807

INCLUDED STARTPACK TRUCK & TRUCK MOBILE

CHARGER

Power in 110-240 V / out 12 V
50/60 Hz
054684



I REGULATED
UoU
FAST CHARGE

FV FLEXIBLE VOLTAGE
85 V → 265 V

054691

OPTION

MEMORY AUTO SAVE
CABLE OBD 1,5 m
054202



Fuse 7,5 A

12/24 V

16Ah + 16Ah INSIDE

HOBBIES OCCASIONAL PRO INTENSIVE

STARTPACK 12.24			
12V	3 600 A	1V DC	900 A
24V	1 800 A	1V DC	700 A

1.8 m - 35 mm² → 600 A 026285
028814

12/24 V

30Ah + 30Ah INSIDE

HOBBIES OCCASIONAL PRO INTENSIVE

STARTPACK PRO 12.24			
12V	6 200 A	1V DC	1300 A
24V	3 100 A	1V DC	1200 A

2 m - 50 mm² → 600 A 026346
028821

INCLUDED STARTPACK 12.24 & PRO 12.24

INTEGRATED CHARGER



Fuse x2
200 A 054547
300 A 054561



DESIGN GYS FRANCE

MADE IN GYS CHINA

MADE IN FRANCE

	Inside	START				TEST	CHARGER INSIDE	EXTERNAL Charge 230V	Protection		Power out		Fuse	Fuse	Dimensions	Weight
		1V/C	Cranking CC	Peak Battery	ON/OFF				Memory	12V DC	12V DC					
STARTPACK TRUCK / TRUCK MOBILE	2x 22 Ah	12V	750 A	1450 A	3200 A	•	—	12V/2 A DC	•	•	12V DC	—	1x300 A	37x20x46 cm	39x22x50 cm	18 kg
		24V	650 A	1300 A	1600 A						12V DC	—	37x20x57 cm	39x24x60 cm	21 kg	
STARTPACK 12.24	2x 16 Ah	12V	900 A	1700 A	3600 A	•	7 A	—	•	•	—	20 A	2x200 A	34x18x46 cm	34x20x51 cm	22 kg
		24V	700 A	1350 A	1800 A						—	20 A	2x200 A	N/A	63x39x30 cm	34 kg
STARTPACK PRO 12.24	2x 30 Ah	12V	1300 A	2400 A	6200 A	•	7 A	—	•	•	—	20 A	2x200 A	N/A	63x39x30 cm	34 kg
		24V	1200 A	2250 A	3100 A						—	20 A	2x200 A	N/A	63x39x30 cm	34 kg

RECOMMENDATION




STARTPACK TRUCK	6V	12V	24V	5 Ah	10 Ah	15 Ah	20 Ah	40 Ah	80 Ah	90 Ah	110 Ah	120 Ah	180 Ah	240 Ah	300 Ah	+ Ah
STARTPACK TRUCK MOBILE	•	•														
STARTPACK 12.24	•	•														
STARTPACK 12.24 PRO	•	•														



STARTPACK

BOOSTERS



SMART STARTER MANAGEMENT SYSTEM

- FULL PROTECTION**
 - On-board electronics
 - Reverse polarity
 - Over voltage
 - No sparks

- AUTO DETECT**
 - Battery voltage detection
 - Microprocessor Control
 - TIMER Adjustable

EXIDE TECHNOLOGIES HIGH QUALITY BATTERIES
 SPIRAL TECHNOLOGY




12/24 V 50Ah SPIRAL + 50Ah SPIRAL **INSIDE**
 HOBBIES OCCASIONAL PRO +++ INTENSIVE


STARTPACK PRO 12.24 XL
 12V **8 500 A** 1V DC 1600 A
 24V **4 250 A** 1V DC 1400 A
 2 m - 70 mm² 1000 A 026711



ENERGY STATION




- 1 AUTONOMOUS BOOSTER**
- 2 CHARGE external batteries**
 2x15A 12V



12/24 V HOBBIES OCCASIONAL PRO INTENSIVE +++

ENERGY STATION 026148
 INTEGRATED CHARGER **WUoU**



MADE IN FRANCE	Inside	START			TEST OK	CHARGER INSIDE	Protection			Power out			Fuse	Fuse	Weight
		1V/C	Cranking CC	Peak Battery			ON/OFF	Memory	Fuse	Memory	Fuse	Weight			
STARTPACK 12.24 XL PRO	2x 50 Ah	12 V	1 600 A	3 000 A	•	6 A outside	• automatic	•	—	300 A	2 m ø 70 mm ²	—	106 x 32 x 35 cm	112 x 35 x 43 cm	68 kg
		24 V	1 400 A	2 600 A											
ENERGY STATION	—	selon batteries/according to battery /je nach Batterie			•	—	•	•	•	—	2,5 m ø 50 mm ²	2 x 30 A	70 x 62 x 92 cm	80 x 53 x 28 cm	37 kg + batteries
		12V	24V	min > max											

RECOMMENDATION	Capacity												Weight			
	6V	12V	24V	5 Ah	10 Ah	15 Ah	20 Ah	40 Ah	80 Ah	90 Ah	110 Ah	120 Ah		180 Ah	240 Ah	300 Ah
STARTPACK PRO 12.24 XL	•	•														> 250 Ah
ENERGY STATION	-	-	-													> 225 Ah

SELECT THE RIGHT BOOSTER

CHOISISSEZ VOTRE BOOSTER • WÄHLEN SIE IHREN BOOSTER AUS

6/12V		12 V								12-24 V				
GYSPACK HERITAGE		GYSPACK 400	GYSPACK AIR	GYSPACK 600	GYSPACK PRO	GYSPACK 660	GYSPACK 700	GYSPACK 750	GYSPACK 900	GYSPACK TRUCK/ TRUCK MOBILE	STARTPACK 12.24	STARTPACK PRO 12.24	STARTPACK PRO 12.24 XL	ENERGY STATION
025844		025455	026322	027336	026155	027862	026254	026179	026278	025448 / 026025	026285	026346	026711	026148
		12 V	12 V	12 V	12 V	12 V								
START	1V/C	400 (6 V)	480 A	480 A	550 A	600 A	640 A	640 A	750 A	830 A	750 (12 V)	900 A (12 V)	1300 A (12 V)	1600 A (12 V)
	CC	450 (12 V)									650 (24 V)	700 A (24 V)	1200 A (24 V)	1400 A (24 V)
	PEAK	800 (6 V)	900 A	900 A	1050 A	1100 A	1200 A	1200 A	1450 A	1700 A	1450 A (12 V)	1700 A (12 V)	2400 A (12 V)	3000 A (12 V)
		850 (12 V)									1300 A (24 V)	1350 A (24 V)	2250 A (24 V)	2600 A (24 V)
		3200 (6 V)	1250 A	1250 A	1750 A	1750 A	1900 A	1800 A	2500 A	3100 A	3200 A (12 V)	3600 A (12 V)	6200 A (12 V)	8500 A (12 V)
	1600 (12 V)									1600 A (24 V)	1800 A (24 V)	3100 A (24 V)	4250 A (24 V)	
		2 x 20 Ah	18 Ah	18 Ah	22 Ah	22 Ah	28 Ah	16 Ah EnerSys	28 Ah EnerSys	30 Ah EnerSys	2 x 22 Ah	2 x 16 Ah EnerSys	2 x 30 Ah EnerSys	2 x 50 Ah EXIDE TECHNOLOGIES
														automatic
		outside 2 A	outside 0,5 A	outside 0,5 A	outside 0,5 A	outside 0,5 A	outside 2 A	inside 2,5 A	outside 2 A	inside 2,5 A	outside 2 A	inside 7 A	inside 7 A	outside 6 A
		Floating	W2	W2	W2	W2	Floating	Floating	Floating	Floating	Floating	Floating	Floating	Floating
		12 V DC	12 V DC	12 V DC	12 V DC	12 V DC								
		1,8 m ø25 mm ²	0,6 m ø16 mm ²	1,1 m ø25 mm ²	0,6 m ø16 mm ²	1,1 m ø25 mm ²	1,3 m ø25 mm ²	1,4 m ø25 mm ²	1,3 m ø25 mm ²	1,8 m ø35 mm ²	1,8 m ø35 mm ²	2 m ø50 mm ²	2 m ø70 mm ²	2,5 m ø50 mm ²
		37x20x46	26x10x29	33x17x37	26x10x29	35x14x37	35x19x40	33x15x32	35x19x40	33x15x32	37x20x46/37x20x57	34x18x46	63x39x30	112x35x43
		18 kg	6,5 kg	8,5 kg	6,5 kg	9 kg	13,5 kg	12 kg	13,5 kg	16 kg	18/21 kg	22 kg	34 kg	68 kg

230V
Après chaque utilisation
After each use
Nach jeder Anwendung
ATTENTION HORS UTILISATION
Laisser le chargeur branché
en permanence.

CAUTION ON STAND BY
Keep your GYSPACK connected to the mains supply.
ACHTUNG WENN NICHT IN GEBRAUCH
Ladegerät dauernd angeschlossen lassen.
ATTENTION CUANDO ESTA APAGADO
Dejar el cargador conectado permanentemente.
OPGELET BIJTEN GEBRUIK
Laat de lader onafgebroken aangesloten.



NATO / OTAN : PRODUITS COMPATIBLES

- Compatible Products - Kompatible Produkte



	p.16-19				p.31	p.38
	GYFLASH 30.12, 50.12 FV 100.12, 101.12 CNT 30.24, 50.24 102.12, 32-12PL	GYFLASH 101.24 CNT FV 121.12 CNT FV	GYFLASH 123.12 CNT FV 103.24 CNT FV 53.48 CNT FV	GYFLASH 15.24 XTREM	STARTIUM 980E	STARTPACK PRO 12.24 XL
NATO CONNECTOR 026780						
Anderson/NATO 5 m - 16 mm ² 026810	✓	—	—	—	—	—
Texas/NATO 5 m - 25 mm ² 025707	—	✓	✓	—	—	—
Texas/NATO 3.5 m - 50 mm ² 025653	—	—	—	—	✓	—
2pts/NATO 5 m - 4 mm ² 025837	—	—	—	✓	—	—
Anderson/NATO 2 m - 25 mm ² 026803	—	—	—	—	—	✓

BATTERIES DE TRACTION : PRODUITS COMPATIBLES

Compatible Products - Kompatible Produkte



IULio BATIUM 25 / 24 p. 27

Specific charge Traction batteries

Pb 9 STEP

- Status analysis
- Recovery
- Sulphation test
- Desulfation
- Fast charge 80%
- Absorption
- Test Absorption
- Refresh
- Floating 100%

Lithium Ready LiFePO₄ 9 STEP

- Status analysis
- UVP Wake Up
- Recovery
- Fast charge 90%
- Absorption 95%
- Test
- Completion
- Equalization
- Floating 100%



Cables Anderson 175A/Texas 5 m - 25 mm ² 025721			
Cables REMA/Texas 5 m - 25 mm ² 025714			

		6 h	7 h	8 h	9 h	10 h	11 h	12 h	13 h	14 h	CURRENT
24 V	BATIUM 25.24	75 Ah	90 Ah	120 Ah	125 Ah	130 Ah	140 Ah	155 Ah	165 Ah	180 Ah	25 A
	GYFLASH 30.24	130 Ah	140 Ah	170 Ah	190 Ah	210 Ah	230 Ah	250 Ah	270 Ah	300 Ah	30 A
	GYFLASH 50.24	210 Ah	230 Ah	280 Ah	315 Ah	350 Ah	380 Ah	415 Ah	450 Ah	500 Ah	50 A
	GYFLASH 101.24	420 Ah	460 Ah	560 Ah	630 Ah	700 Ah	760 Ah	830 Ah	900 Ah	1000 Ah	100 A
48 V	GYFLASH 103.24	420 Ah	460 Ah	560 Ah	630 Ah	700 Ah	760 Ah	830 Ah	900 Ah	1000 Ah	100 A
	GYFLASH 53.48	210 Ah	230 Ah	280 Ah	315 Ah	350 Ah	380 Ah	415 Ah	450 Ah	500 Ah	50 A



NOMADPOWER PRO

BOOSTERS

LITHIUM INSIDE

3 IN 1



START ENGINE



POWER BANK



LIGHT

3 modes



NEW 12 2020

LED x 28



45

NOMADPOWER PRO

BOOSTERS (Lithium inside)

12 V

NP PRO 700

600 A

12 V



027510

028838

INCLUDED



12 / 24 V

NP PRO TRUCK

600 A

12 V

600 A

24 V



027527

028845

INCLUDED



12 V • XL

NP PRO 12 XL

1000 A

12 V



025912

INCLUDED



24 V • XL

NP PRO 24 XL

1400 A

24 V



025905

INCLUDED



	LITHIUM		I				J	START	CABLE	SMART CABLES	INPUT	MICRO USB	OUTPUT	POWER SUPPLY		LIGHT	MODES	cm	kg
	CAPACITY/CELL	FULL CHARGE	Start	Cranking CC	Peak Battery	3s								PHONE	LAPTOP				
NP PRO 700	6 Ah - 92.5 Wh	9h	600 A	1500 A	2000 A	14000 J	12 V, PETROL & DIESEL	—	MULTI SECURITIES	9V/2 A 12V/1.5 A	5V/2 A (Type C)	5V/2.4 - 9V/2 A - 12V/1.5 A - 15V/10 A	•	2	—	1 x LED	LIGHT / S.O.S. / SPOT	22.8 x 10 x 3.8	0.82
NP PRO TRUCK	5,3 Ah - 137 Wh	10h	600 A	1500 A	2000 A	12 V: 14000 J 24 V: 35000 J	12 V/24 V, PETROL & DIESEL	—	MULTI SECURITIES Integrated	9V/2 A 12V/1.5 A	5V/2 A (Type B)	5V/1 A - 5V/2.1 A 12V/10 A	•	2	•	1 x LED	LIGHT / S.O.S. / SPOT	24.8 x 24.8 x 9.6	2.4
NP PRO 12XL	8 Ah - 118.4 Wh	10h	1000 A	1800 A	3000 A	18000 J	12 V, PETROL & DIESEL	—	12 V/15 A 4 A	—	18 V/2 A	5V/2.1 A - 12V/3.5 A - 12V/10 A - 19V/3.5 A	•	2	•	28 x LED	LIGHT / S.O.S. / SPOT	27.4 x 27.8 x 11	5.6
NP PRO 24XL	8 Ah - 236.8 Wh	10h	1400 A	2400 A	3000 A	60000 J	24 V, PETROL & DIESEL	—	12 V/15 A 4 A	—	18 V/2 A	5V/2.1 A - 12V/3.5 A - 12V/10 A - 19V/3.5 A	•	2	•	28 x LED	LIGHT / S.O.S. / SPOT	27.4 x 27.8 x 11	5.6



Recommendation

NP PRO 700

NP PRO TRUCK

NP PRO 12XL

NP PRO 24XL

NP PRO 700									
NP PRO TRUCK									
NP PRO 12XL									
NP PRO 24XL									

OPTION

MEMORY AUTO SAVE CABLE OBD 1,5 m for NOMAD POWER 15, 20, 30, PRO 700 027534





BOOSTERS

SUPER CAPACITORS INSIDE

SANS BATTERIE - BATTERYLESS
- OHNE BATTERIE

NEW TECHNOLOGY - FULL ELECTRONIC CONTROL



- ✓ NO BATTERY INSIDE
- ✓ NO MAINTENANCE
- ✓ ALWAYS READY
- ✓ BOOSTER SANS BATTERIE INTERNE
- ✓ AUCUNE MAINTENANCE
- ✓ TOUJOURS PRÊT
- ✓ KEINE INTERNE BATTERIE
- ✓ KEINE WARTUNG
- ✓ IMMER BEREIT

EASY TO USE

2 minutes!



-40/+65°C

STARTRONIC 800

800 A 12 V GO > 5 V

026735



5x **800 F** INSIDE

INCLUDED

CIGARETTE LIGHTER for Easy charge
STARTRONIC 800 & HYBRID 950
027404



STARTRONIC HYBRID 950

SUPERCAPACITORS + LITHIUM

950 A 12 V GO > 1 V

026117



5x **950 F** + Lithium INSIDE

INCLUDED STARTRONIC HYBRID 950

Lithium battery



027411



Cables 100% Cu
25 mm² - 1.7 m

SMART STARTER



SMART STARTER MANAGEMENT SYSTEM

FULL PROTECTION -40/+65°C

SUPERCAPACITORS

- ✓ 1 MILLION CYCLES
- ✓ ULTRA FAST CHARGE
- ✓ NO CHARGE STORAGE
- ✓ UNLIMITED STARTS

INCLUDED



5x **3400 F** INSIDE **GYSCAP 680E**
1600 A 12 V GO > 1 V
026773

Homologations / Approvals / Zulassungen:
PSA17.1716

MADE IN CHINA

MADE IN FRANCE

	START 1V / C	Number of Capacitors	Integrated Inverter	INPUT CHARGE Charging time				internal lithium battery	cm	kg			
				OFF	ON	OFF	ON						
STARTRONIC 800	800 A	12 V	5 × 800 F	•	4 min	60 s	4 min	4 min	5V/2 A	40 min	-	26,7 × 19,5 × 5	1,86
STARTRONIC HYBRID 950	950 A	12 V	5 × 950 F	•	4 min	60 s	4 min	4 min	5V/2 A	40 min	•	25 × 18,5 × 6	1,86
GYSCAP 680E	1600 A	12 V	5 × 3400 F	—	—	120 s	—	15 min	—	—	—	35 × 44 × 19	8,2

Recommendation

STARTRONIC 800

STARTRONIC HYBRID 950

GYSCAP 680 E



TESTERS



TRADITIONAL

TBP 100

12 V 20 > 100 Ah

055131



TBP 500

12 V 10 > 160 Ah

055148



x6 Languages
Sprachen

Bluetooth



NOT INCLUDED

Download on the App Store
GET IT ON Google Play

HIGH TECH BT MOBILITY
TRACK DATA by E-devices



x4 Languages
Sprachen



Download on the App Store
GET IT ON Google Play




ELECTRONIC & CONNECTED

BTW 300 DHC

6/12 V 7 > 240 Ah

056664



Wireless battery monitor Indicateur de charge sans fil

12/24 V 7 > 240 Ah

024212



LED

BT 001

12 V 7 > 230 Ah

056640



NUMERIC

NBT 100

12 V 20 > 150 Ah

024151



NBT 200

12 V 20 > 150 Ah

024168



ALTERNATOR 12 V

x1 Languages
Sprachen



x10 Languages
Sprachen



x9 Languages
Sprachen




DIGITAL

DBT 300

12 V 4 > 150 Ah


024175



DBT 350

12 V 7 > 240 Ah


025868



DBT 400

6/12 V 7 > 240 Ah

024182



MADE IN CHINA

MADE IN TAIWAN

MADE IN CHINA

MADE IN TAIWAN

	BATTERY	TEST				PRINT PAPER	DIGITAL	RESULT	TEMPERATURE COMPENSATION	cm	kg
		BATTERY A	BATTERY V	CHARGE & START SYSTEM VEHICLE							
TBP 100	6-12V	20 > 100 Ah	•	•	12V	—	—	5/10s	15 min	16x1.8x30	1.5
TBP 500	12V	10 > 160 Ah	•	•	12V	—	—	15s	15 min	27x26x13	3.75
BTW 300 DHC	6-12V	7 > 240 Ah	•	min 1.5V	12/24V	—	—	1s	instant	10x3x7	0.33
BATTERY MONITOR	12-24V	7 > 240 Ah	—	min 7V	12/24V	—	—	1s	instant	6,5x5 x1,5	0.1
BT 001	12V	7 > 230 Ah	—	•	12V	—	LED	1s	instant	3x12x1,5	0.29
NBT 100	12V	20 > 150 Ah	•	min 7 V	—	—	•	1s	instant	7x1.5x12	0.25
NBT 200	12V	20 > 150 Ah	•	min 7 V	12V	—	•	1s	instant	7x1.5x12	0.25
DBT 300	12V	4 > 150 Ah	•	min 4,5 V	12V	—	rétro-éclairé /back-lit	1s	instant	12x7.9x22.7	0.25
DBT 350	12V	7 > 240 Ah	•	min 8 V	12 / 24V	—	rétro-éclairé /back-lit	1s	instant	9.6x3x13.8	0.8
DBT 400	6-12V	7 > 240 Ah	•	min 1,5 V	12 / 24V	—	rétro-éclairé /back-lit	1s	instant	11.5x5x19	0.8

i Recommendation	TEST		LIQUID	START /STOP ENGINE	EFB	AGM VRLA/GEL	CURRENT CCA SAE
	batteries/Battery/Ladegeräte	Circuit alterateur/ Alternator Circuit/Lichtmaschinenchaltkreis					
TBP 100	6V 12V	12V	•	—	—	—	20 > 100 Ah
TBP 500	12V	12V	•	—	—	—	10 > 160 Ah
BTW 300 DHC	6V 12V	12V 24V	•	•	•	•	7 > 240 Ah 40 > 2000 A
BATTERY MONITOR	12V 24V	12V 24V	•	•	•	•	7 > 240 Ah
BT 001	12V	12V	•	•	•	•	7 > 230 Ah
NBT 100	12V	—	•	—	—	—	20 > 150 Ah 200 > 1200 A
NBT 200	12V	—	•	—	—	—	20 > 150 Ah 200 > 1200 A
DBT 300	12V	—	•	—	•	•	4 > 150 Ah 40 > 1200 A
DBT 350	12V	12V 24V	•	•	•	•	7 > 240 Ah 40 > 2000 A
DBT 400	6V 12V	12V 24V	•	•	•	•	7 > 240 Ah 40 > 2000 A



PBT

TESTERS

+ PRINTER

x8 Languages Sprachen



x5 Languages Sprachen



x10 Languages Sprachen



x9 Languages Sprachen



GESTION LOGICIELLE DE LA BATTERIE
BATTERY-MANAGEMENT SOFTWARE
SOFTWARE BATTERIE MANAGEMENT

x10 Languages Sprachen



NEW



GESTION LOGICIELLE DE LA BATTERIE
BATTERY-MANAGEMENT SOFTWARE
SOFTWARE BATTERIE MANAGEMENT

PRINTER • 12 V

PRINTER • 6/12 V

PRINTER • 6/12/24 V (2x12)

PBT 550

12 V 30 > 220 Ah

START STOP ALTERNATOR 12 V

024199



x2 (included)
056633

PBT 600

12 V 30 > 220 Ah

START STOP ALTERNATOR 12/24 V

024205



x2 (included)
056633

PBT 700

12 V 7 > 240 Ah

START STOP ALTERNATOR 12/24 V

024229



x1 (included)
056237

BT2010 START-STOP DHC

6/12 V 7 > 240 Ah

START STOP ALTERNATOR 12/24 V

055339



x1 (included)
056237

PBT 824

6/12/24(2X12)V 7 > 240 Ah

START STOP ALTERNATOR 12/24 V

025738



x1 (included)
056237

056220	056237	056633
x2	x1	x2
37 mm	57 mm	57 mm
7.5 m	28 m	7.5 m
25 mm	50 mm	25 mm
BT 301	RT 777	PBT 550
BT 501	PBT 700	PBT 600
	PBT 824	PBT 700
	BT 2010	PBT 824
		BT 2010
		SPM

Languages - Sprachen

GB	FR	DE	IT	ES	PT	CZ	NL	PL	RU	TR
DBT 300										
DBT 350										
DBT 400										
PBT 550										
PBT 600										
PBT 700										
BT 2010										
PBT 824										
BTW 300DHC										

50

	TEST	A	V	CHARGE & START SYSTEM VEHICLE	PRINT PAPER	DIGITAL	RESULT	TEMPERATURE COMPENSATION	cm	kg	
											MADE IN CHINA
PBT 550	12V	30 > 220 Ah	min 6V	12V	•	rétro-éclairé /back-lit	1s	instant	•	55x25	0.55
PBT 600	12V	30 > 220 Ah	min 8V	12/24V	•	rétro-éclairé /back-lit	1s	instant	•	55x25	1.1
PBT 700	12V	7 > 240 Ah	min 8V	12/24V	•	rétro-éclairé /back-lit	1s	instant	•	23.5x10.2x6.8	0.7
BT 2010 DHC	6-12V	7 > 240 Ah	min 1.5V	12/24V	•	rétro-éclairé /back-lit	1s	instant	•	13x6.4x25.1	0.7
PBT 824	6-12-24 (2x12)V	7 > 240 Ah	min 1.5V	12/24V	•	rétro-éclairé /back-lit 4 colors	1s	instant	•	25x4.5x13	0.7

i Recommendation	TEST	batteries/Battery/Ladegeräte	Circuit alterateur/Alternator Circuit/Lichtmaschinen Schaltkreis	PRINT PAPER	LIQUID					CURRENT CCA SAE
					LIQUID	START/STOP ENGINE	EFB	AGM VRLA/GEL		
PBT 550	12V		12V	•	•	•	•	•	30 > 220 Ah	100 > 2000 A
PBT 600	12V		12V 24V	•	•	•	•	•	30 > 220 Ah	100 > 2000 A
PBT 700	12V		12V 24V	•	•	•	•	•	7 > 240 Ah	40 > 2000 A
BT 2010 DHC	6V 12V		12V 24V	•	•	•	•	•	7 > 240 Ah	40 > 3000 A
PBT 824	6V 12V 24V (2X12)		12V 24V	•	•	•	•	•	7 > 240 Ah	40 > 2000 A



POWER INVERTER

12 V • 24 V > 230 V



CONVERGYS 150

12 V

027022
027039



CONVERGYS 300

12 V

027053
027046



12 V CONVERGYS

Recommendation

	CONVERGYS 150	CONVERGYS 300	PSW600W	PSW 1000W	PSW 1500W 12 V	PSW 1500W 24 V	MSW82000	70 Ah	200 Ah
Electroménager Home Appliance									
Micro-Ondes - Microwave					700 - 1000 W			30 - 50 min	1 h 30 - 2 h
Grille Pain - Toaster					800 - 1500 W			20 - 40 min	1 h - 2 h
Refrigérateur - Fridge (40 L)					45 W			12 h	35 h
Bouilloire - Kettle					700 - 2500 W			15 - 45 min	35 min - 2 h
Cafetière espresso - Espresso coffee maker					1000 - 1600 W			20 - 30 min	1 h - 1 h 30
Cafetière filtre - Drip coffee maker					800 - 1200 W			25 - 40 min	1 h 30 - 2 h
Électronique Electronic									
Téléphone - Mobile phone					5 - 10 W			55 - 110 h	155 - 310 h
Ordinateur portable - Laptop					60 - 95 W			5 - 9 h	16 - 28 h
Radio					10 - 40 W			14 - 55 h	40 - 155 h
TV 15"					40 W			13 h 30	39 h
TV 21"					50 W			11 h	31 h
Console de jeux vidéo - Video game console					39 - 100 W			5 - 13 h	16 - 39 h
Appareil photo - Camera					4 - 19 W			25 - 135 h	78 - 390 h
Confort Comfort									
Eclairage - Light				100 W				5 h 30	16 h
Chauffage électrique - Electrical heater						1800 - 2500 W		12 - 20 min	35 - 45 min
Ventilateur - Fan				50 W				11 h	31 h
Sèche cheveux - Hairdryer						1000 - 2000 W		15 - 30 min	45 min - 1 h 30
Maritime Sailing									
Feux de navigation - Navigation lights				24 W				30 h	80 h
Radar				24 W				30 h	80 h
Pilote automatique - Autopilot mode				60 W				9 h	30 h
GPS - GPS/Sat nav.				6 W				110 h	310 h

MADE IN CHINA

	Power	Peak power	Pure Sin Wave	Optimum Efficiency	Input DC	Output AC	Output USB (2.1) DC	max 150W	Universal	5m	6 x 10 x 5 cm	0,5 kg
CONVERGYS 150	150W	300W	—	90,5 %	12V	230V	5V - 2 A	•	—	—	6 x 10 x 5 cm	0,5 kg
CONVERGYS 300	300W	600W	—	85 %	12V	230V	5V - 2 A	•	•	—	10 x 15 x 6 cm	0,95 kg
PSW 600W-12	600W	1200W	•	85 %	12V	230V	5V - 2 A	—	cables	•	23 x 31 x 15 cm	2,2 kg
PSW 1000W-12	1000W	2000W	•	85 %	12V	230V	5V - 2 A	—	cables	•	23 x 39 x 15 cm	3,4 kg
PSW 1500W RC-12	1500W	3000W	•	85 %	12V	230V	5V - 2 A	—	cables	•	23 x 39 x 15 cm	3,6 kg
PSW 1500W-24	1500W	3000W	•	85 %	24V	230V	5V - 2 A	—	cables	•	23 x 39 x 15 cm	3,6 kg
MSW 82000	2000W	4000W	—	80 %	24V	230V	5V - 2 A	—	cables	•	35 x 20 x 9,8 cm	5,8 kg



PSW 600W-12

12 V

027275
027343



PSW 1000W-12

12 V

027282
027350



Remote Control (5 m)
Included

- Tension faible / Surtension / Surcharge / Surchauffe / Court-circuit
- Low volt / Over volt / Over load / Overheating / Output short-circuit
- Niedervolt / Überspannung / Überlastung / Überhitzung / Kurzschluss am Ausgang



PSW 1500W RC-12

12 V

027701
027732

INCLUDED

all PSW



12 V

PURE SINE WAVE



MSW 82000

24 V

027237
027244



PSW 1500W-24

24 V

027305
027374

24 V MSW MODIFIED SINE WAVE

24 V PSW PURE SINE WAVE

JUMPER CABLES

320 A > 1000 A

056374										
056381										
056206										
564015										
056404										
056190										
056602										
056312										
056329										
056336										
027695										
056343										
056558										
056541										
056619										

INSULATED CLAMPS & LED

PINCES ISOLÉES - INSULATED CLAMPS - ISOLIERTE KLEMMEN
 • Pinzas aisladas • Garras isoladas • Geïsoleerde klemmen
 • Μονωμένοι ακροδέκτες
 • Изолированные зажимы • 绝缘充电夹ιοιοι



		ESSENCE BENZINE PETROL	DIESEL		
MADE IN CHINA					
056381	500 A	5,5l	4,5l	3,5 m	25 mm ²

PRO BRASS CLAMPS

PINCES LAITON, NON ISOLÉES - Brass clamps, NOT INSULATED - Messingklemmen, nicht isoliert
 • Pinzas de latón, no aisladas • Koperen klemmen, niet geïsoleerd • Garras bronce, latão isoladas
 • Ακροδέκτες χαλκού χωρίς μόνωση • ЛАТУННЫЕ ЗАЖИМЫ, НЕИЗОЛИРОВАННЫЕ • 黄铜夹, 无绝缘



056206	320 A	3 m	—	16 mm ² (CCA)
564015	500 A	3 m	—	25 mm ² (CCA)
056404	700 A	4,5 m	—	35 mm ² (CCA)
056602	1000 A	5,1 m	—	50 mm ² (100% Cu)
MADE IN FRANCE				
056190	1000 A	4,5 m	INCLUDED	50 mm ² (100% Cu)

PRO INSULATED CLAMPS

PINCES ISOLÉES - INSULATED CLAMPS - ISOLIERTE KLEMMEN - Pinzas aisladas
 • Garras aisladas • Geïsoleerde klemmen • Μονωμένοι ακροδέκτες
 • Изолированные зажимы • 绝缘充电夹ιοιοι



		ESSENCE BENZINE PETROL	DIESEL				DIN 72553
MADE IN CHINA							
056312	200 A	1,5l		2,8 m	—	10 mm ²	—
056329	320 A	2,5l		3 m	—	16 mm ²	•
056336	500 A	5,5l	3l	3,5 m	—	25 mm ²	•
056343	700 A	7l	4l	4,5 m	—	35 mm ²	•
MADE IN FRANCE							
056558	1000 A	7l	4l	4,5 m	INCLUDED	50 mm ² (100% Cu)	—

CÂBLES DE DÉMARRAGE - BOOSTER CABLES - Starterkabel - CABLES DE ARRANQUE - CAVI DI AVVIAMENTO



TEST VOLT

LED




		ESSENCE BENZINE PETROL	DIESEL		
DIN 72553					
027695	350 A	5,5l	3l	3,5 m	25 mm ²

SUPER PRO INSULATED CLAMPS

PINCES ISOLÉES - INSULATED CLAMPS - ISOLIERTE KLEMMEN - Pinzas aisladas
 • Garras aisladas • Geïsoleerde klemmen • Μονωμένοι ακροδέκτες
 • Изолированные зажимы • 绝缘充电夹



MADE IN FRANCE



056541	700 A	4,5 m	35 mm ²



ANTI-ARC PROTECTION x2



MADE IN FRANCE



056619	1000 A	5 m	50 mm ²

ACCESSOIRES



Pince ampèremétrique - 400 A
 - Clamp-on ammeter - 053991
 - Strommesszange - 600 A
 - 053984

HIGH FLEXIBILITY ELECTRICAL CABLES

Ø	L	054882	054875	A (60%)	A (35%)
10 mm ²	100 m	054882	054875	88	92
16 mm ²	100 m	054905	054899	120	130
25 mm ²	100 m	054929	054912	164	184
35 mm ²	100 m	054943	054936	210	240
50 mm ²	100 m	054967	054950	273	320
70 mm ²	50 m	—	056565	310	380

CABLES EN 60246-5/H01N2-D (Caoutchouc - Rubber)

Ø	L	046801	A (60%)	A (35%)
50 mm ²	100 m	046801	273	320
70 mm ²	≈ x m	046832	348	417
95 mm ²	≈ x m	046863	430	525

PINCES - Clamps - Klemmen - Pinzas - Garras - Ακροδέκτες - Зажимы - 充电夹

40 A	60 A	200 A	300 A	600 A	650 A	700 A	850 A	1000 A	300 A	600 A
↔ 30 mm	↔ 25 mm	↔ 38 mm	↔ 45 mm	↔ 40 mm	↔ 35 mm	↔ 28 mm	↔ 44 mm	↔ 55 mm	↔ 38 mm	↔ 38 mm
2.5 mm ²	6 mm ²	16 mm ²	25 mm ²	35 mm ²	25 mm ²	25 mm ²	35 mm ²	70 mm ²	50 mm ²	95 mm ²
053106	055537 055520 024816	053502 053403	053700 053601	053779 053786	055551 055544	025783 025776	053816 053793	025769 025752	038059	038066

COSSES BATTERIE - Battery Terminal - Polklemmen - Terminales batería - Accupool - Terminais de batería - Πόλος μπαταρίας - Контакты аккумуляторной - батареи - 电池端子

Ø 10 mm / 35 mm ²	Ø 13 mm / 50 mm ²	Ø 16 mm / 70 mm ²
054400	054431 054448	054332 054349
x25	x25	x25
+	+	+
-	-	-

COSSES - Cable lugs - Terminal Kabelschuhe - Kabelschoen

16 mm ²	M10	×10	038219
25 mm ²	M10	×10	038226
35 mm ²	M14	×10	038233
50 mm ²	M14	×10	038240
75 mm ²	M16	×10	038257
125 mm ²	M15	×5	038264

NETTOYEUR COSSES / BORNES - Cleaning brush poles / terminals



QUICK CONNECTORS



FUSIBLES - Fuses - Sicherungen - Fusibles - Zekeringen - Fusíveis - Ασφάλειες - Плавкие предохранители - 保险丝

6.3 A	054578	10 A	054530	15 A	054493	20 A	054509	25 A	054516	30 A	054523	40 A	054554
10 A	056527	100 A	054486	100 A	054394	150 A	027930	200 A	054547	250 A	055568	300 A	054561
15 A	054578	100 A	054486	100 A	054394	150 A	027930	200 A	054547	250 A	055568	300 A	054561

PROTECTION ANTI-ARC - Anti-arc protection - Lichtbogenschutz - Protección anti-arco - Piekspanningsbeveiliging - Protecção anti-faisca - Αντι-σπινθηρική προστασία - Защита против дуги - 抗电弧保护



PORTE-BATTERIE AJUSTABLE - Adjustable battery carrier - Einstellbarer Batteriehalter

100 ~ 180 mm



PÈSE ACIDE ANTIGEL - Acidimeter (PH Meter) - Säure/Frostschutzmittel-Tester - Acido densimetro anticongelante - Zuurweger - Medidor de PH (ácido) - Μετρητής οξύτητας (PH) - Αцидиметр (pH-метр) - 防冻酸度计

054103



KIT SOLAIRE DE MAINTIEN DE CHARGE AVEC ACCESSOIRES - Solar powered charger with accessories - Solarpanel zur Ladeerhaltung mit Zubehör - Kit solar de mantenimiento de carga - Солнечная панель для поддержания заряда в наборе с аксессуарами




STATION MULTICHARGE POUR BATTERIES - Multi charge station for batteries - Multi-Ladestation für Starterbatterien



SAUVEGARDE MÉMOIRE OBD - Memory auto save - Sicherung des Speichers - Salvaguardia memorias - Salvaguardas de memória - Αυτόματη αποθήκευση ρυθμίσεων - Сохранение настроек - 记忆储存器



GYSPACK OBD
054998
055001



INSIDE	MEMORY SAVER	Dimensions	Weight
12V - 7 Ah	< 4 A	25 × 18 × 25 cm	3 kg



CABLE OBD - Cable OBD - Kabel für OBD

054202
Fuse 7,5 A
1,5 m



LAMPE BALADEUSE

- Hand Lamp
- Handleuchte

100-250 lumens (x3)

TRIPODE 250 L
3 x 1 W COB LED

3 x 3.6 V
300 mAh
AAA rechargeable,
Ni-MH, USB
charging (6h)

operating time
High position: 1 h
Low position: 3 h
Flashing: 5 h

↓ 260 x 100
x 100 mm

059955



400 lumens

400 L
COB LED

Li-ion
Charging time: 8h

operating time
High position: 2.5 h
Low position: 5 h
Top light (1 W): 6 h

↓ 230 x 65 x 40 mm

059153



250-600 lumens

PRO 600 L
COB LED, 80 CRI

3.7 V - 2200 mAh Li-ion
micro USB charging (3.5 h)

operating time:
High position: 1.5 h,
Mid position: 4.5 h,
Top light (100 lumens):
10 h

↓ 190
x 56
x 29 mm
IP 54
210g

060883



200-400 lumens

ÉTANCHE 400 L
COB LED

3.7 V - 2000 mAh Li-ion
USB charging (4/6 h)

operating time
High position: 2 h
Mid position: 4 h
Top light (4 W): 3 h

↓ 285 x 65 x 65 mm
IP 56

059948



Étanche -
Waterproof

LAMPE INSPECTION

- Inspection Lamp
- Inspektionslampen

100-200 lumens

MINI 200 L
COB LED, 80 CRI, 6500 K

3.7 V - 700 mAh Li-ion
micro USB charging (2.5 h)

operating time
High position: 1.5 h
Low position: 4 h
Top light: 3.5 h

IP 20
↓ 76 g, ↓ 174 x 27.5 x 28 mm

060852



50 > 500 lumens

FLEXIBLE 500 L
COB LED - 80 CRI+
6500 K

3.7 V - 2600 mAh Li-ion
USB charging (4 h)

operating time
High position: 2 h
Low position: 16 h
Top light: 9.5 h

IP 54
↓ 290 g
↓ 423 x 65.5
x 44.5 mm

060869



100-280 lumens

FRONTALE 280 L
3 W COB LED
80 CRI+, 6500 K

3.7 V - 1500 mAh Li-po
micro USB charging

operating time
High position: 2 h
Low position: 6 h

IP 65, ↓ 110 g
↓ 78.5 x 47.5 x 42 mm

060845



0 > 600 lumens


PRO 600 L
6500 K

3.7 V - 2600 mAh Li-ion

operating time
1.5 > 15 h

↓ 380 x 40 x 45 mm
300 g
057760

058309



120 lumens



charge indicator

motion
detection mode

060845



USB charging
/Power supply

LAMPE SOUS CAPOT

- Under bonnet lamp
- Leuchte für Motorhaube

300-600 lumens

600 L
120 COB LED

3.7 V - 4000 mAh Li-ion
charging time: 10/12 h

operating time
High position: 1.5 h
Low position: 3 h

1.3 kg

059962



250-800 lumens


800 L
120 COB LED

3.7 V - 4000 mAh Li-ion
charging time: 10/12 h

operating time
High position: 3 h
Low position: 6 h

058002

058316



PROJECTEUR SUR TRÉPIED


- Worklight with tripod
- Arbeitsleuchte mit Standfuß

1800 lumens

1800 L
3x 55 COB LED
total 165 LED

1.8 m power cord

059146



3000 lumens

3000 L
35 W COB LED

2 m power cord

IP 44

059979



4000 lumens

Lampe sur TRÉPIED
4000 L

Worklight with tripod
3x 20 COB LED,
total 60 LED



3 m
power cord

059986



BATTERIES DE DÉMARRAGE - Automotive batteries - Starterbatterien - Baterías de arranque - Automotive accu's - Baterías de Automóvil - Μπαταρίες οχημάτων - Пусковые батареи - 汽车启动电池

W	LIQUID		START/STOP (A)	GEL Sealed	OPTIMA maXXima	Graphs
	CALCIUM	Silver/AGMv				
W	★	★	★	★	★	Graphs
W2	★	★	★	★	★	Graphs
WU	★	★	★	★	★	Graphs
WUoU	★	★	★	★	★	Graphs
IWUoU	★	★	★	★	★	Graphs
I REGULATED IUoU FAST CHARGE	★	★	★	★	★	Graphs
GYSFLASH Pb 7/8 STEP	★	★	★	★	★	Graphs
GYSFLASH Lithium 8 STEP	LiFePO4 / Li-ion / Li-Po / NMC / LCO / MCO / NCA...					Graphs



MARKETING

Podium de présentation
Display stand
Podest
(machines not included)

063204
A: 45 cm, B: 50 cm, C: 50 cm
063211
A: 80 cm, B: 50 cm, C: 50 cm

A - Barnum 3 x 3 m
098022
B - Open Barnum 2 x 2 m
098039
C - Oriflamme 1,75 x 0,50 m
098015

FA1 FA2 SB1

Linéaire de vente
avec 2 étagères
- Retail display space
with 2 shelves
- Lochwandregal
mit 2 Böden

060784

Type	FA1	FA2	SB1
complet - complete - komplett	062429	062443	061149
sans linéaire - without display stand - ohne Regal	062436	062450	062412

Catalogs and posters available
for download on our website
www.gys.fr

24V / 240Ah



GYS FRANCE

HEADQUARTER

1 rue de la Croix des Landes
CS 54159
53941 Saint-Berthevin - Cedex
Laval - France
Tel +33 2 43 01 23 60
E-mail service.client@gys.fr



ZI, 134 bd des Loges
53941 Saint-Berthevin
Laval - France

LOGISTIC CENTER

2 Rue Jean Dausset
53910 Changé - France
Tel +33 2 43 01 54 33



INVEST IN THE FUTURE



French manufacturer
since 1964

INVEST IN THE FUTURE

www.gys.fr



GYS GERMANY

Professor-Wieler
Straße 11
52070 Aachen
Deutschland

Tel +49 241 / 189-23-710
Fax +49 241 / 189-23-719
E-mail aachen@gys.fr



GYS ITALIA

Vega - Parco Scientifico Tecnologico
di Venezia
Via Delle Industrie, 25/4
30175 Marghera - VE
Italia

Tel +39 041 53 21 565
E.mail italia@gys.fr

LinkedIn



Youtube



GYS UK

Unit 3
Great Central Way
Rugby - Warwickshire
CV21 3XH
United Kingdom

Tel +44 1926 338 609
Fax +44 1926 429 764
E-mail uk@gys.fr



GYS CHINA

Lot N°15
6666 bd Songze
201706 Qingpu Shanghai
China

Tel +86 6221 4461
Fax +86 5226 0067
www.gys-china.com.cn
E-mail contact@gys-china.com.cn

WeChat



Distributed by

2
0
2
0
B

sstarif 095083

Document non contractuel. GYS se réserve le droit de modifier sans préavis les spécifications de ses appareils.
Document not contractual. GYS reserves the right to modify the specifications of the machines without prior notice. Irrtümer und Änderungen vorbehalten. • I.P. - 174 g

